

UD2 Series

Profile

A small, affordable, energy efficient hardware platform that can be VESA mounted on the back of a monitor. The DVI-I port supports dual monitors with an optional Y-Cable and it can connect to common peripherals with its four USB ports.



Features

- Slim design.
- VESA mountable.
- Dualview support.
- Excellent price performance.

Benefits

- The perfect companion for any workplace due to the small form factor and the latest design.
- Mountable on the back of a monitor with the optional available VESA bracket. Ideal for space constrained environments.
- The DVI-I port offers the possibility to connect one digital and one analog monitor via the optional Y-Cable.
- Can run any firmware package at a competitive price.



Networking Infrastructure Solutions



Member of the initiative Energy Efficiency made in Germany,
Federal Ministry of Economics and Technology



UD2 – Specifications

System	
Available Operating Systems	IGEL Linux (LX) Microsoft® Windows® Embedded Standard 2009 (ES) Microsoft® Windows® Embedded CE 6.0 (CE)
Management	IGEL Universal Management Suite included
Form Factor	Standard
Processor	VIA Eden 400 MHz
Chipset	VIA CN700
Memory	
RAM	IGEL Linux: 512 MB Windows CE: 512 MB Windows Embedded Standard: 1 GB
Flash Memory	IGEL Linux: 1 GB Windows CE: 512 MB Windows Embedded Standard: 2 GB
Graphics	
Chipset	VIA Unichrome Pro
Video Memory	16-64 MB shared memory
Ports	1x DVI-I (DVI-to-VGA adapter included)
Supported Resolutions	1920 x 1200 (LX & ES) , 1280 x 1024 (CE)
Network	
Ethernet	10/100 Base-T
Audio	
Chipset	AC97 compatible
Ports	Front: 1x line-out, 1x mic-in
Speakers	1x internal
Peripheral interfaces	
PS/2	1x keyboard
Serial	Optional, via USB-to-Serial adapter
Parallel	Optional, via USB-to-Parallel adapter
USB 2.0	4x back
Dimensions	
Device (DxWxH)	203 x 65 x 208 mm
Packaging (DxWxH)	268 x 112 x 264 mm
Weight	1.2 kg
Environment	
Cooling	Fanless convection
Operation noise	0 db
Operating Temperature	Vertical: 0 to 40 °C Horizontal: 0 to 35 °C (optional)
Operating Humidity	10% – 80%, non-condensing
Power	
Input	Auto sensing 100~240 VAC / 50~60 Hz
Power Supply	External
Power Consumption: Idle / Sleep Mode	13W / 2W
Options	
VESA mount	For mounting on the back of a monitor.
Rubber feet	For horizontal placement of the device.
DualView Y-Cable	For DVI-I to DVI-D + VGA. Connect two monitors.
USB-to-Serial adapter	For connecting peripherals that require a serial port.
USB-to-Parallel adapter	For connecting printers that require a parallel port.

Connectivity options



Product color options



www.igel.com/en/evaluation

Germany (HQ)
IGEL Technology GmbH
Hanna-Kunath-Str. 31
D-28199 Bremen
Germany
Tel +49 (0) 421 52094 0
Fax +49 (0) 421 52094 1499

United Kingdom
IGEL Technology Ltd
1210 Parkview
Arlington Business Park
Theale · Reading · Berkshire
RG7 4TY · UK
Tel +44 (0) 118 340 3400
Fax +44 (0) 118 340 3411

United States
IGEL Technology Inc.
2106 Florence Avenue
Cincinnati
OH 45206 · USA
Tel +1 954 739 9990
Fax +1 954 739 9991
Toll Free (US only):
+1 877 GET IGEL
info@igelamerica.com

Singapore
IGEL Technology
Care of: C. Melchers GmbH & Co.
Singapore Branch
101 · Thomson Road
24-01/05 United Square
Singapore 307591
Tel +65 6259 9288
Fax +65 6259 9111

Hong Kong
IGEL Technology
Care of: Melchers (H.K.) Ltd.
1210 Shun Tak Centre
West Tower
168-200 Connaught Road C.
Hong Kong
Tel +852 25469069
Fax +852 25596552

Standard are 2 years thin client warranty for end customers (after date of delivery). After an online registration this warranty will be extended for one year. IGEL is a registered trademark of IGEL Technology GmbH. All hardware and software names are registered trademarks of the respective manufacturers. Errors and omissions excepted. Subject to change without notice. ©2/2010 IGEL Technology info@igel.com 83-EN-10-3

